

EPS / EPH Elbow

External conduit fitting



External hinged elbow

One-piece elbow fittings allow a variety of conduit size variations. These fittings are designed to snap together over all types of slit and unslit conduit, maintaining maximum conduit bore. Can be used as an in-line reducer as well as an enlarger.

Harnessflex® X-Temp™

Protection at temperatures between 200°C to -50°C with high vibration, dynamic conditions.

EPS / EPH External elbow

Part No.	X-Temp™ Part No.	Conduit size (NC / NW / US)			Nominal dimensions (mm)				
		A	B	C	D	E	F	G	
EPS08S08*	EPH08S08	08 / 7.5 / ¼	08 / 7.5 / ¼	38.0	29.0	20.0	10.0	10.0	
EPS12S12*	EPH12S12	12 / 10 / ⅝ ₁₆	12 / 10 / ⅝ ₁₆	38.0	29.0	20.0	10.0	10.0	
EPS1608	EPH1608	16 / 10 / ⅝ ₁₆	08 / 7.5 / ¼	34.0	34.0	21.0	10.0	10.0	
EPS1612	EPH1612	16 / 13 / ¾	12 / 10 / ⅝ ₁₆	34.0	34.0	21.0	10.0	10.0	
EPS1616	EPH1616	16 / 13 / ¾	16 / 13 / ¾	34.0	34.0	21.0	10.0	10.0	
EPS2008	EPH2008	20 / 17 / ½	08 / 7.5 / ¼	41.0	39.0	26.0	12.0	10.0	
EPS2012	-	20 / 17 / ½	12 / 10 / ⅝ ₁₆	41.0	41.0	26.0	10.0	10.0	
EPS2016	EPH2016	20 / 17 / ½	16 / 13 / ¾	41.0	41.0	26.0	12.0	10.0	
EPS2020	EPH2020	20 / 17 / ½	20 / 17 / ½	41.0	41.0	26.0	12.0	12.0	
EPS2520	-	25 / 22 / ¾	20 / 17 / ½	48.0	48.0	33.0	13.0	12.0	
EPS2525	-	25 / 22 / ¾	25 / 22 / ¾	48.0	48.0	33.0	13.0	13.0	
EPS2812	-	28 / 23 / ¾	12 / 10 / ⅝ ₁₆	48.0	48.0	33.0	13.0	10.0	
EPS2816	-	28 / 23 / ¾	16 / 13 / ¾	48.0	48.0	33.0	13.0	10.0	
EPS2820	-	28 / 23 / ¾	20 / 17 / ½	48.0	48.0	33.0	13.0	12.0	
EPS2825	-	28 / 23 / ¾	25 / 22 / ¾	48.0	48.0	33.0	13.0	13.0	
EPS2828	-	28 / 23 / ¾	28 / 23 / ¾	48.0	48.0	33.0	13.0	13.0	
EPS3232	-	32 / 29 / 1	32 / 29 / 1	60.0	60.0	38.0	12.0	12.0	
EPS4040	-	40 / 36 / 1 ¼	40 / 36 / 1 ¼	67.0	67.0	47.0	15.0	15.0	

*Swivel fitting / Colours available: Black ● RAL 9005 (Standard) / Brown ● RAL 8016 (X-Temp™).